TECHNICAL DATA

EUROMOLL® RANGE



Article:	EUROMOLL® 4710I, 4710L
Description:	Self-adhesive sealing gasket tape in cross linked (physical) polyethylene foam with completely closed cells and one adhesive side
Carrier:	Polyethylene foam
Density:	30kg/m³ *(ISO EN UNI 845)*
Adhesive	acrylic
Color:	White - Anthracite
Tensile strength	Longitudinal : 395 Kpa Transversal : 250 Kpa *(ISO 1926)*
Compression strength	10% 19Kpa 25 % 38Kpa 50% 105 Kpa *(ISO 844)*
Adhesion:	19 N/25 mm *(FINAT-METHOD FTM 1)*
Thermal conductivity	0.034 W/mK A 10 °C 0.039 W/mK A 40 °C

Temperature resistance: -80° +100°C

Protective liner: 4710I : No (direct application)
4710L : yes

Thickness (foam):

I (without liner)	L (with liner)
4710I: 2mm	4710L : 2mm
4711I: 3mm	4711L : 3mm
4712I: 4mm	4712L : 4mm
4713I: 5mm	4713L : 5mm
4714I: 6mm	4714L : 6mm
4714I: 8mm	4714L : 6mm
4716I: 9mm	4716L : 9mm
4717I: 10mm	4717L : 10mm

Properties:
Impermeable
Putrefaction resistant
Not toxic